

Where **Ideas** Become **Solutions**

www.estexmfg.com

ESTEX



SINCE 1900

TITAN RATED DIRT TARP



What does 'TITAN RATED' mean for the equipment?

Our overhead rated products are designed for the working professional in sensitive environments where overhead lifting is required. All TITAN line products are **Independent 3rd party Load Tested and Certified** with a certificate of compliance provided.

Certified for the maximum Safe Working Load Limit, each product has a **unique serial number provided** to facilitate tracking and inspection protocols.

- **SAFE WORKING LOAD OF 2970 LBS.**
- Minimizes the repetitive motion of shoveling, creating a **high ergonomic value**
- Maximizes customer relations while minimizing the effect on the landscaping
- Used to hold and move dirt during pole change out procedure
- Made of heavy-duty materials for your toughest jobs
- Easy to maintain and store
- Eases cleanup because soil and/or tools are contained in one spot

2864-6DTR

6ft x 6ft
Titan Rated Cargo/Dirt Tarp

2864-8DTR

8ft x 8ft
Titan Rated Cargo/Dirt Tarp

2864-10DTR

10ft x 10ft
Titan Rated Cargo/Dirt Tarp

toll free: 1-800-749-1224
phone: 770-964-3322
fax: 770-964-7534

P. O. Box 368
402 East Broad Street
Fairburn, GA 30213

04/13

ESTEX MANUFACTURING CO. INC

402 E. BROAD ST WWW.ESTEXMFG.COM
FAIRBURN, GA 30213
USA

CERTIFIED SAFE WORKING LOAD 1350 KG / 2976 LBS

Part Number **2864-8DTR** METHOD OF LIFTING: USE FOUR ATTACHMENT POINTS
Serial Number **8DT-1234567** WHEN NOT IN USE: PROTECT FROM DIRECT SUN

Manufacture Date

DO NOT REMOVE THIS LABEL

Limitation on Usage:

Safe Operating Temperature Range is 0 deg. C and 100 deg. C.

Chemical Exposure:

Do not use when exposed to liquid acids or phenolics.

Inspections:

Each day before use the dirt tarp and each of the webbing lifting eyes shall be inspected for damage or defect and if found be removed from service. (See Data Safety Sheet for complete inspection and use details). Protect from Direct Sunlight when not in use.

Warning:

The user is responsible to determine that this product is appropriate for the intended use and complies with all laws and regulatory standards. The user assumes all risks associated with the use of this product. Estex Mfg. Co. Inc shall not be liable for any loss, injury or death arising out of use of this product.

Lifting Instructions:

Use all four points of attachment for lifting.

COMPETITION	ESTEX TITAN BRAND
SELF CERTIFIED	INDEPENDANT 3RD PARTY CERTIFIED
CAPACITY TESTED	LOAD TESTED TO DESTRUCTION
NON-QC CAPABLE: NO SERIAL NUMBER	TRACKABLE SERIAL NUMBER
NO SAFETY MARGIN	HAS SAFETY MARGIN